

BYD127

ULTRA FAST LOW-LOSS RECTIFIER


PRV : 200 Volts
Io : 2.0 Amperes

FEATURES :

- * Glass passivated
- * High maximum operating temperature
- * Low leakage current
- * Excellent stability
- * Smallest surface mount rectifier outline
- * **Pb / RoHS Free**

MECHANICAL DATA :

- * Case : Molded plastic
- * Terminals : Plated Terminals, solderable per MIL-STD-750 Method 2026
- * Polarity : Color band denotes cathode end
- * Mounting position : Any
- * Weight : 0.116 gram



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Rating at 25 °C ambient temperature unless otherwise specified

RATING	SYMBOL	VALUE	UNIT
Maximum Repetitive Peak Reverse Voltage	V_{RRM}	200	V
Maximum Continuous Reverse Voltage	V_R	200	V
Maximum Average Forward Current (Note 1)	$I_{F(AV)}$	2.0	A
Maximum Non-Repetitive Peak Forward Surge Current (Note 2)	I_{FSM}	15	A
Maximum Forward Voltage at $I_F = 1.0$ A, $T_J = 25$ °C	V_F	0.93	V
Maximum Reverse Current at $V_R = V_{RRMmax}$	I_R	2.0	μ A
	$I_{R(H)}$	50	μ A
Maximum Reverse Recovery Time (Note 3)	T_{rr}	25	ns
Thermal Resistance from Junction to Tie-Point	$R_{th\ j-tp}$	30	K / W
Thermal Resistance from Junction to Ambient (Note 4)	$R_{th\ j-a}$	150	K / W
Junction Temperature Range	T_J	- 65 to + 175	°C
Storage Temperature Range	T_{STG}	- 65 to + 175	°C

Notes :

- (1) $T_{tp} = 95$ °C; averaged over any 20 ms period; see Fig. 1 and 2.
- (2) $t = 10$ ms half sine wave; $T_J = T_{jmax}$ prior to surge; $V_R = V_{RRMmax}$.
- (3) Reverse Recovery Test Conditions : $I_F = 0.5$ A, $I_R = 1.0$ A, $I_{rr} = 0.25$ A.
- (4) Device mounted on an epoxy-glass printed-circuit board, 1.5 mm thick; thickness of Cu-layer ≥ 40 μ m.

RATING AND CHARACTERISTIC CURVES (BYD127)

FIG.1 - MAXIMUM PERMISSIBLE AVERAGE FORWARD CURRENT AS A FUNCTION OF TIE-POINT TEMPERATURE




FIG.2 - MAXIMUM STEADY STATE POWER DISSIPATION AS A FUNCTION OF AVERAGE FORWARD CURRENT




FIG.3 - FORWARD CURRENT AS FUNCTION OF FORWARD VOLTAGE; TYPICAL VOLTAGE




FIG.4 - REVERSE CURRENT AS FUNCTION OF REVERSE VOLTAGE; TYPICAL VALUES

