

# BYD57D - BYD57V

## ULTRA-FAST SOFT-RECOVERY CONTROLLED AVALANCHE RECTIFIERS


**PRV : 200 - 1400 Volts**  
**Io : 1.0 - 1.2 Amperes**

### FEATURES :

- \* Glass passivated
- \* High maximum operating temperature
- \* Low leakage current
- \* Excellent stability
- \* Guaranteed avalanche energy absorption capability
- \* Smallest surface mount rectifier outline
- \* **Pb / RoHS Free**

### MECHANICAL DATA :

- \* Case : Molded plastic
- \* Terminals : Plated Terminals, solderable per MIL-STD-750 Method 2026
- \* Polarity : Color band denotes cathode end
- \* Mounting position : Any
- \* Weight : 0.116 gram



### MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Rating at 25 °C ambient temperature unless otherwise specified.


RATING	SYMBOL	BYD	BYD	BYD	BYD	BYD	BYD	BYD	UNIT
		57D	57G	57J	57K	57M	57U	57V	
Maximum Repetitive Peak Reverse Voltage	$V_{RRM}$	200	400	600	800	1000	1200	1400	V
Maximum Continuous Reverse Voltage	$V_R$	200	400	600	800	1000	1200	1400	V
Min. Reverse Avalanche Breakdown Voltage @ $I_R = 0.1 \text{ mA}$	$V_{(BR)R-min}$	300	500	700	900	1100	1300	1500	V
Maximum Average Forward Current	$I_{F(AV)}$	1.0 <sup>(1)</sup>					1.2 <sup>(1)</sup>		A
		0.4 <sup>(2)</sup>							
Maximum Non-Repetitive Peak Forward Surge Current (Note 3)	$I_{FSM}$	5							A
Maximum Repetitive Peak Forward Current at $T_{tp} = 85 \text{ °C}$	$I_{FRM}$	8.5					11		A
Maximum Forward Voltage at $I_F = 1.0 \text{ A}$ ; $T_J = 25 \text{ °C}$	$V_F$	3.6					2.3		V
Maximum Reverse Current at $V_R = V_{RRMmax}$ $T_J = 25 \text{ °C}$ $T_J = 165 \text{ °C}$	$I_R$	5.0							$\mu\text{A}$
	$I_{R(H)}$	100							$\mu\text{A}$
Maximum Reverse Recovery Time (Note 4)	$T_{rr}$	30			75		150		ns
Thermal Resistance from Junction to Tie-Point	$R_{th \text{ j-tp}}$	30							K / W
Thermal Resistance from Junction to Ambient (Note 5)	$R_{th \text{ j-a}}$	150							K / W
Junction Temperature Range	$T_J$	- 65 to + 175							°C
Storage Temperature Range	$T_{STG}$	- 65 to + 175							°C

#### Notes :


- (1)  $T_{tp} = 85 \text{ °C}$ ; see Fig. 1 and 2; averaged over any 20 ms period; see also Fig.5 and 6.
- (2)  $T_{amb} = 60 \text{ °C}$ ; PCB mounting; see Fig. 3 and 4; averaged over any 20 ms period; see also Fig.5 and 6.
- (3)  $t = 10 \text{ ms}$  half sine wave;  $T_j = T_{jmax}$  prior to surge;  $V_R = V_{RRMmax}$ .
- (4) Reverse Recovery Test Conditions :  $I_F = 0.5 \text{ A}$ ,  $I_R = 1.0 \text{ A}$ ,  $I_{rr} = 0.25 \text{ A}$ .
- (5) Device mounted on an epoxy-glass printed-circuit board, 1.5 mm thick; thickness of Cu-lay  $\geq 40 \text{ }\mu\text{m}$ .

## RATING AND CHARACTERISTIC CURVES ( BYD57D - BYD57V )


**FIG.1 - MAXIMUM PERMISSIBLE AVERAGE FORWARD CURRENT AS A FUNCTION OF TIE-POINT TEMPERATURE**




**FIG.2 - MAXIMUM PERMISSIBLE AVERAGE FORWARD CURRENT AS A FUNCTION OF TIE-POINT TEMPERATURE**




**FIG.3 - MAXIMUM PERMISSIBLE AVERAGE FORWARD CURRENT AS A FUNCTION OF AMBIENT TEMPERATURE**




**FIG.4 - MAXIMUM PERMISSIBLE AVERAGE FORWARD CURRENT AS A FUNCTION OF AMBIENT TEMPERATURE**



**FIG.5 - MAXIMUM STEADY STATE POWER DISSIPATION AS A FUNCTION OF AVERAGE FORWARD CURRENT**




**FIG.6 - MAXIMUM STEADY STATE POWER DISSIPATION AS A FUNCTION OF AVERAGE FORWARD CURRENT**




**RATING AND CHARACTERISTIC CURVES ( BYD57D- BYD57V )**

**FIG.7 - FORWARD CURRENT AS FUNCTION OF FORWARD VOLTAGE**



**FIG.8 - FORWARD CURRENT AS FUNCTION OF FORWARD VOLTAGE**



**FIG.9 - REVERSE CURRENT AS FUNCTION OF JUNCTION TEMPERATURE**

