

EL1Z

ULTRA FAST RECOVERY RECTIFIER DIODES


PRV : 200 Volts
Io : 1.5 Ampere

FEATURES :

- * High current capability
- * High surge current capability
- * High reliability
- * Low reverse current
- * Low forward voltage drop
- * Fast switching for high efficiency
- * Pb / RoHS Free

MECHANICAL DATA :

- * Case : DO-41 Molded plastic
- * Epoxy : UL94V-O rate flame retardant
- * Lead : Axial lead solderable per MIL-STD-202, Method 208 guaranteed
- * Polarity : Color band denotes cathode end
- * Mounting position : Any
- * Weight : 0.339 gram



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Rating at 25 °C ambient temperature unless otherwise specified.
 Single phase, half wave, 60 Hz, resistive or inductive load.
 For capacitive load, derate current by 20%.

| RATING | SYMBOL | VALUE | UNIT |
|---|--------|---------------|------|
| Maximum Peak Reverse Voltage | VRM | 200 | V |
| Maximum Peak Reverse Surge Voltage | VRSM | 200 | V |
| Maximum Average Rectified Forward Current | IF(AV) | 1.5 | A |
| Maximum Peak Forward Surge Current (50 Hz, Half-cycle, Sine wave, Single Shot) | IFSM | 20 | A |
| Maximum Forward Voltage at IF = 1.5 A | VF | 0.98 | V |
| Maximum Reverse Current at Reverse voltage | IR | 100 | µA |
| Maximum Reverse Current at Reverse voltage Ta = 100 °C | IR(H) | 500 | µA |
| Maximum Reverse Recovery Time (Note 1) | Trr | 50 | ns |
| Junction Temperature Range | TJ | - 40 to + 150 | °C |
| Storage Temperature Range | TSTG | - 40 to + 150 | °C |

Notes :

(1) Reverse Recovery Test Conditions : IF = 100 mA, IRP = 100 mA.

RATING AND CHARACTERISTIC CURVES (EL1Z)

FIG.1 - REVERSE RECOVERY TIME CHARACTERISTIC AND TEST CIRCUIT DIAGRAM




FIG.2 - DERATING CURVE FOR OUTPUT RECTIFIED CURRENT




FIG.3 - MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT




FIG.4 - TYPICAL FORWARD CHARACTERISTICS




FIG.5 - TYPICAL REVERSE CHARACTERISTICS

