

GP15A - GP15M

PRV : 50 - 1000 Volts

Io : 1.5 Amperes


FEATURES :

- * High current capability
- * High surge current capability
- * High reliability
- * Low reverse current
- * Low forward voltage drop
- * Pb / RoHS Free

MECHANICAL DATA :

- * Case : D2 Molded plastic
- * Epoxy : UL94V-O rate flame retardant
- * Lead : Axial lead solderable per MIL-STD-202, Method 208 guaranteed
- * Polarity : Color band denotes cathode end
- * Mounting position : Any
- * Weight : 0.465 gram

SILICON RECTIFIER DIODES



Dimensions in inches and (millimeters)

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Rating at 25 °C ambient temperature unless otherwise specified.
Single phase, half wave, 60 Hz, resistive or inductive load.
For capacitive load, derate current by 20%.

RATING	SYMBOL	GP 15A	GP 15B	GP 15D	GP 15G	GP 15J	GP 15K	GP 15M	UNIT
Maximum Recurrent Peak Reverse Voltage	VRRM	50	100	200	400	600	800	1000	V
Maximum RMS Voltage	VRMS	35	70	140	280	420	560	700	V
Maximum DC Blocking Voltage	VDC	50	100	200	400	600	800	1000	V
Maximum Average Forward Current 0.375"(9.5mm) Lead Length Ta = 55 °C	IF(AV)	1.5							A
Maximum Peak Forward Surge Current, 8.3ms Single half sine wave Superimposed on rated load (JEDEC Method)	IFSM	50							A
Maximum Peak Forward Voltage at IF = 1.5 A	VF	1.1							V
Maximum Full load Reverse Current, Full Cycle Average 0.375",(9.5mm) Lead Length Ta = 55°C	IR(AV)	100							µA
Maximum DC Reverse Current Ta = 25 °C	IR	5.0							µA
at Rated DC Blocking Voltage Ta = 150 °C	IR(H)	200							µA
Typical Reverse Recovery Time (Note 1)	Trr	2.0							µs
Typical Junction Capacitance (Note 2)	CJ	15							pf
Typical Thermal Resistance (Note 3)	RθJA	25							°C/W
Junction Temperature Range	TJ	- 65 to + 175							°C
Storage Temperature Range	TSTG	- 65 to + 175							°C

Notes :

- (1) Reverse Recovery Test Conditions : IF = 0.5 A, IR = 1.0 A, Irr = 0.25 A.
- (2) Measured at 1.0 MHz and applied reverse voltage of 4.0 VDC
- (3) Thermal Resistance from Junction to Ambient at 0.375" (9.5mm) Lead Lengths, P.C. Board Mounted.

RATING AND CHARACTERISTIC CURVES (GP15A - GP15M)

FIG.1 - DERATING CURVE FOR OUTPUT RECTIFIED CURRENT




FIG.2 - MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT




FIG.3 - TYPICAL FORWARD CHARACTERISTICS




FIG.4 - TYPICAL REVERSE CHARACTERISTICS

