

SHV- 04

PRV : 4000 Volts
I_o : 2 mA


FEATURES :

- * Glass passivated junction chip
- * High voltage capability
- * High surge current capability
- * High reliability
- * Low reverse current
- * **Pb / RoHS Free**

MECHANICAL DATA :

- * Case : DO-41 Molded plastic
- * Epoxy : UL94V-O rate flame retardant
- * Lead : Axial lead solderable per MIL-STD-202, Method 208 guaranteed
- * Polarity : Color band denotes cathode end
- * Mounting position : Any
- * Weight : 0.34 gram

HIGH VOLTAGE RECTIFIER DIODE



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Rating at 25 °C ambient temperature unless otherwise specified.

RATING	SYMBOL	VALUE	UNITS
Maximum Peak Reverse Voltage	V_{RM}	4000	V
Maximum Average Forward Current	$I_{F(AV)}$	2.0	mA
Peak Forward Surge Current 50 Hz half-wave single	I_{FSM}	0.5	A
Maximum Peak Forward Voltage at $I_F = 10$ mA.	V_F	20	V
Maximum Reverse Current at $V_R = V_{RM}$, $T_a = 25$ °C $T_a = 100$ °C	I_R	1.0	μA
	$I_{R(H)}$	3.0	μA
Operating Junction Temperature Range	T_J	- 40 to + 150	°C
Storage Temperature Range	T_{STG}	- 40 to + 150	°C