

SM8S SERIES

SURFACE MOUNT TRANSIENT VOLTAGE SUPPRESSOR

Stand-off Voltage: 10 to 43 Volts
 Peak Pulse Power: 6600W(10/1000 μ s)
 : 5200W(10/10,000 μ s)

FEATURES :

- * Excellent clamping capability
- * Low incremental surge resistance
- * Fast response time : typically less than 1.0 ps from 0 volt to $V_{BR(min.)}$
- * Dual Diode construction
- * Pb / RoHS Free


MECHANICAL DATA

- * Case : D²PAK(TO-263)
- * Epoxy : UL94V-O rate flame retardant
- * Lead : Surface Mount per J-STD-020C, Method 208 guaranteed
- * Polarity : Heatsink is Anode
- * Mounting position : Any
- * Weight : 1.7 grams (approximately)

DEVICES FOR UNIPOLAR APPLICATIONS

For uni-directional without "C"
 Electrical characteristics apply in both directions

**** Under Development ****



Maximum Ratings and Thermal Characteristics (T_c = 25°C unless otherwise noted)

Rating	Symbol	Value	Unit
Peak Pulse Power Dissipation with 10/1000 μ s waveform 10/10,000 μ s waveform	P _{PPM}	6600 5200	W
Steady State Power Dissipation	P _D	8.0	W
Peak Forward Surge Current, 8.3ms Single Half Sine-Wave	I _{FSM}	700	A
Typical Thermal Resistance Junction to Case	R _{θJC}	0.9	°C/W
Operating and Storage Temperature Range	T _J , T _{STG}	- 55 to + 175	°C

ELECTRICAL CHARACTERISTICS (Ta = 25°C)

TYPE	Breakdown Voltage @ I_T			Reverse Stand off Voltage	Maximum Reverse Leakage @ V_{RWM}	Maximum Reverse Leakage @ V_{RM}	Maximum Peak Pulse Current at 10/1000 μ s	Maximum Clamping Voltage @ I_{PPM}
	V_{BR} (V)		I_T	V_{RWM}	I_D	$I_D (T_C=175^\circ C)$	I_{PPM}	V_C
	Min.	Max.	(mA)	(V)	(μ A)	(μ A)	(A)	(V)
SM8S10C	11.1	13.6	5.0	10	15	250	351	18.8
SM8S10CA	11.1	12.3	5.0	10	15	250	388	17.0
SM8S11C	12.2	14.9	5.0	11	10	150	328	20.1
SM8S11CA	12.2	13.5	5.0	11	10	150	363	18.2
SM8S12C	13.3	16.3	5.0	12	10	150	300	22.0
SM8S12CA	13.3	14.7	5.0	12	10	150	332	19.9
SM8S13C	14.4	17.6	5.0	13	10	150	277	23.8
SM8S13CA	14.4	15.9	5.0	13	10	150	307	21.5
SM8S14C	15.6	19.1	5.0	14	10	150	256	25.8
SM8S14CA	15.6	17.2	5.0	14	10	150	284	23.2
SM8S15C	16.7	20.4	5.0	15	10	150	245	26.9
SM8S15CA	16.7	18.5	5.0	15	10	150	270	24.4
SM8S16C	17.8	21.8	5.0	16	10	150	229	28.8
SM8S16CA	17.8	19.7	5.0	16	10	150	254	26.0
SM8S17C	18.9	23.1	5.0	17	10	150	216	30.5
SM8S17CA	18.9	20.9	5.0	17	10	150	239	27.6
SM8S18C	20.0	24.4	5.0	18	10	150	205	32.2
SM8S18CA	20.0	22.1	5.0	18	10	150	226	29.2
SM8S20C	22.2	27.1	5.0	20	10	150	184	35.8
SM8S20CA	22.2	24.5	5.0	20	10	150	204	32.4
SM8S22C	24.4	29.8	5.0	22	10	150	168	39.4
SM8S22CA	24.4	26.9	5.0	22	10	150	168	35.5
SM8S24C	26.7	32.6	5.0	24	10	150	153	43.0
SM8S24CA	26.7	29.5	5.0	24	10	150	170	38.9
SM8S26C	28.9	35.3	5.0	26	10	150	142	46.6
SM8S26CA	28.9	31.9	5.0	26	10	150	157	42.1
SM8S28C	31.1	38.0	5.0	28	10	150	132	50.1
SM8S28CA	31.1	34.4	5.0	28	10	150	145	45.4
SM8S30C	33.3	40.7	5.0	30	10	150	123	53.5
SM8S30CA	33.3	36.8	5.0	30	10	150	136	48.4
SM8S33C	36.7	44.9	5.0	33	10	150	112	59.0
SM8S33CA	36.7	40.6	5.0	33	10	150	124	53.3
SM8S36C	40.0	48.9	5.0	36	10	150	103	64.3
SM8S36CA	40.0	44.2	5.0	36	10	150	114	58.1
SM8S40C	44.4	54.3	5.0	40	10	150	92	71.4
SM8S40CA	44.4	49.1	5.0	40	10	150	102	64.5
SM8S43C	47.8	58.4	5.0	43	10	150	86	76.7
SM8S43CA	47.8	52.8	5.0	43	10	150	95	69.4

Notes:

- (1) For all types maximum $V_F = 1.8V$ at $I_F = 100A$ measured on 8.3ms single half sine-wave or equivalent square wave, duty cycle = 4 pulses per minute maximum
- (2) " SM S " will be omitted in marking on the diode.

RATING AND CHARACTERISTIC CURVES (SM8S SERIES)

FIG. 1 - POWER DERATING CURVE




FIG. 2 - LOAD DUMP POWER CHARACTERISTICS
(10ms EXPONENTIAL WAVEFORM)




FIG. 3 - PULSE WAVEFORM




FIG. 4 - REVERSE POWER CAPABILITY




FIG. 5 - TYPICAL TRANSIENT THERMAL IMPEDANCE

