



GP02-20 ~ GP02-40

PRV : 2000 - 4000 Volts
Io : 0.25 Ampere


HIGH VOLTAGE GLASS PASSIVATED JUNCTION SILICON RECTIFIER

FEATURES :

- * Glass passivated junction
- * High current capability
- * High surge current capability
- * High reliability
- * Low reverse current
- * Low forward voltage drop
- * Pb / RoHS Free

MECHANICAL DATA :

- * Case : DO-41 Molded plastic
- * Epoxy : UL94V-O rate flame retardant
- * Lead : Axial lead solderable per MIL-STD-202, Method 208 guaranteed
- * Polarity : Color band denotes cathode end
- * Mounting position : Any
- * Weight : 0.339 gram



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Rating at 25 °C ambient temperature unless otherwise specified.

Single phase, half wave, 60 Hz, resistive or inductive load.

For capacitive load, derate current by 20%.

RATING	SYMBOL	GP02-20	GP02-25	GP02-30	GP02-35	GP02-40	UNIT
Maximum Recurrent Peak Reverse Voltage	V _{RRM}	2000	2500	3000	3500	4000	V
Maximum RMS Voltage	V _{RMS}	1400	1750	2100	2450	2800	V
Maximum DC Blocking Voltage	V _{DC}	2000	2500	3000	3500	4000	V
Maximum Average Forward Current 0.375"(9.5mm) Lead Length Ta = 55 °C	I _{F(AV)}	0.25					A
Peak Forward Surge Current 8.3 ms. Single half sine wave Superimposed on rated load (JEDEC Method)	I _{FSM}	15					A
Maximum Forward Voltage at 1.0 A	V _F	3.0					V
Maximum DC Reverse Current Ta = 25 °C at Rated DC Blocking Voltage Ta = 100 °C	I _R	5.0					μA
	I _{R(H)}	50					μA
Typical Reverse Recovery Time (Note 1)	T _{rr}	2.0					μs
Typical Junction Capacitance (Note 2)	C _J	3.0					pF
Typical Thermal Resistance (Note 3)	R _{θJA}	130					°C/W
Junction Temperature Range	T _J	- 65 to + 175					°C
Storage Temperature Range	T _{STG}	- 65 to + 175					°C

Notes :

- (1) Reverse Recovery Test Conditions : I_F = 0.5 A, I_R = 1.0 A, I_{rr} = 0.25 A.
- (2) Measured at 1.0 MHz and applied reverse voltage of 4.0 VDC
- (3) Thermal Resistance from Junction to Ambient at 0.375"(9.5mm) Lead Lengths, P.C. Board Mounted.

RATING AND CHARACTERISTIC CURVES (GP02-20 ~ GP02-40)

FIG. 1 - DERATING CURVE FOR OUTPUT RECTIFIED CURRENT




FIG. 2 - MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT




FIG. 3 - TYPICAL FORWARD CHARACTERISTICS




FIG. 4 - TYPICAL REVERSE CHARACTERISTICS




FIG 5 . - TYPICAL JUNCTION CAPACITANCE

