

# SHV- 05JS

## HIGH VOLTAGE RECTIFIER DIODE

**PRV : 2500 Volts**

**I<sub>o</sub> : 30 mA**

### FEATURES :

- \* Glass passivated junction chip
- \* High voltage capability
- \* High surge current capability
- \* High reliability
- \* Low reverse current
- \* Low forward voltage drop
- \* High voltage diode for Igniters
- \* Pb / RoHS Free

### MECHANICAL DATA :

- \* Case : DO-41 Molded plastic
- \* Epoxy : UL94V-0 rate flame retardant
- \* Lead : Axial lead solderable per MIL-STD-202,  
Method 208 guaranteed
- \* Polarity : Color band denotes cathode end
- \* Mounting position : Any
- \* Weight : 0.34 gram

### MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Rating at 25 °C ambient temperature unless otherwise specified.

RATING	SYMBOL	VALUE	UNITS
Maximum Peak Reverse Voltage	V <sub>RM</sub>	2500	V
Maximum Average Forward Current	I <sub>F(AV)</sub>	30	mA
Peak Reverse Surge Current 50 Hz half-wave single	I <sub>RSM</sub>	3	A
Maximum Peak Forward Voltage at I <sub>F</sub> = 10 mA.	V <sub>F</sub>	5.0	V
Maximum Reverse Current at V <sub>R</sub> = V <sub>RM</sub>	I <sub>R</sub>	10	µA
Zener Voltage at I <sub>R</sub> = 100 µA	V <sub>Z(Min.)</sub>	2.6	kV
	V <sub>Z(Max.)</sub>	5.0	
Operating Junction Temperature Range	T <sub>J</sub>	- 40 to + 150	°C
Storage Temperature Range	T <sub>STG</sub>	- 40 to + 150	°C

