

RB521S-30

SCHOTTKY BARRIER DIODE

PRV : 30 Volts

I_O : 200 mA

FEATURES :


- * Extremely small surface mounting type
- * High reliability
- * Pb / RoHS Free

APPLICATIONS :

- * Low current rectification

MECHANICAL DATA :

- * Lead finish : 100% Matte Sn (Tin)
- * Mounting position : Any
- * Qualified max reflow temperature : 260 °C



Maximum Ratings and Thermal Characteristics (T_a = 25 °C)

Parameter	Symbol	VALUE	Unit
Maximum DC Reverse Voltage	V _R	30	V
Mean Rectifying Current	I _O	200	mA
Maximum Peak Forward Surge Current	I _{FSM}	1.0	A
Junction Temperature	T _J	125	°C
Storage temperature range	T _{STG}	-40 to + 125	°C

Electrical Characteristics (T_a = 25 °C)

Parameter	Symbol	Test Condition	Min	Typ	Max	Unit
Reverse Current	I _R	V _R = 10 V	-	-	30	μA
Forward Voltage	V _F	I _F = 200 mA	-	-	0.5	V

RATING AND CHARACTERISTIC CURVES (RB521S-30)

FIG.1 - DERATING CURVE




FIG.2 - CAPACITANCE BETWEEN TERMINALS CHARACTERISTICS




FIG.3 - TYPICAL FORWARD CHARACTERISTICS




FIG. 4 - TYPICAL REVERSE CHARACTERISTICS

